

**00110**

SOCKET FOR 1SN / R1AT HOSE

| PART NO. | HOSE SIZE | | DIMENSIONS | | | | |
|--------------|-----------|------|------------|------|------|--|--|
| | DN | DASH | L | D | d | | |
| 00110-03AZ | 5 | 03 | 23 | 18.5 | 12.6 | | |
| 00110-04AZ * | 6 | 04 | 27.4 | 21 | 14 | | |
| 00110-05AZ * | 8 | 05 | 28 | 21.5 | 15.6 | | |
| 00110-06AZ * | 10 | 06 | 30 | 24.3 | 18 | | |
| 00110-08AZ * | 12 | 08 | 34 | 28 | 21.5 | | |
| 00110-10AZ * | 16 | 10 | 37 | 31.3 | 24.5 | | |
| 00110-12AZ * | 20 | 12 | 42 | 35.5 | 28.7 | | |
| 00110-16AZ * | 25 | 16 | 51 | 43.5 | 36.3 | | |
| 00110-20Z * | 32 | 20 | 59 | 52 | 45 | | |
| 00110-24Z * | 40 | 24 | 74 | 58 | 51.5 | | |
| 00110-32Z * | 50 | 32 | 78 | 72 | 65 | | |

1. Part no. marked with "*" is recommended.

2. Matched with braid fitting and ISO 1436 1SN & R1ATS, GB/T 3683 1SN & R1ATS, EN 853 1SN, SAE J517 100R1AT braid hose, and no-skive needed.

3. Material options for socket.

| Socket material | Part. No. suffix | Part No. example |
|------------------------|------------------|------------------|
| Carbon steel (Default) | Z | 00110-08AZ |
| 304 stainless steel | SR | 00110-08ASR |
| 316L stainless steel | SV | 00110-08ASV |
| 316Ti stainless steel | SY | 00110-08ASY |

4. Plating options and performance for carbon steel socket

| Plating method | Part. No. suffix | Part No. example | White rust (Hours) | Red rust(Hours) |
|------------------------|------------------|------------------|--------------------|-----------------|
| Cr3+ plating (Default) | Z | 00110-08AZ | 96 | 360 |
| Durakote plating | ZD | 00110-08AZD | 360 | 720 |
| Zinc-nickel plating | ZN | 00110-08AZN | 1000 | - |