



00401-D

SOCKET FOR 4SH HOSE

| PART NO. | HOSE SIZE | | DIMENSIONS | | | | |
|--------------|-----------|------|------------|------|------|--|--|
| | DN | DASH | L | D | d | | |
| 00401-20DZ * | 32 | 20 | 66 | 53 | 43 | | |
| 00401-24DZ * | 40 | 24 | 71 | 60.5 | 50 | | |
| 00401-32DZ * | 50 | 32 | 79 | 76 | 65.2 | | |

- Part no. marked with "*" is recommended.
- Matched with spiral fitting and ISO 3862 4SH, GB/T 10544 4SH, EN 856 4SH spiral hose.
- Material options for socket.

| Socket material | Part. No. suffix | Part No. example |
|------------------------|------------------|------------------|
| Carbon steel (Default) | Z | 00401-20DZ |
| 304 stainless steel | SR | 00401-20DSR |
| 316L stainless steel | SV | 00401-20DSV |
| 316Ti stainless steel | SY | 00401-20DSY |

- Plating options and performance for carbon steel socket

| Plating method | Part. No. suffix | Part No. example | White rust (Hours) | Red rust (Hours) |
|------------------------|------------------|------------------|--------------------|------------------|
| Cr3+ plating (Default) | Z | 00401-20DZ | 96 | 360 |
| Durakote plating | ZD | 00401-20DZD | 360 | 720 |
| Zinc-nickel plating | ZN | 00401-20DZN | 1000 | - |