

**03310**

SOCKET FOR 2SN / R2AT HOSE

PART NO.	HOSE SIZE		DIMENSIONS				
	DN	DASH	L	D	d		
03310-03Z	5	03	23	21	14.1		
03310-04Z	6	04	30.5	23	15.7		
03310-05Z	8	05	30	24	17.3		
03310-06Z	10	06	32	26	19.6		
03310-08Z	12	08	34	29	22.8		
03310-10AZ	16	10	35	34.5	26.6		
03310-12Z	20	12	42	37	30.3		
03310-16Z	25	16	51	46.7	38.8		
03310-20AZ	32	20	55	59	49.6		
03310-24AZ	40	24	66	67	56		
03310-32AZ	50	32	72	80	68.8		

1. Part no. marked with "\*" is recommended.

2. Matched with braid fitting and ISO 1436 2SN & R2ATS, GB/T 3683 2SN & R2ATS, EN 853 2SN, SAE J517 100R2AT braid hose, and no-skive needed.

3. Material options for socket.

Socket material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	03310-08Z
304 stainless steel	SR	03310-08SR
316L stainless steel	SV	03310-08SV
316Ti stainless steel	SY	03310-08SY

4. Plating options and performance for carbon steel socket

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	03310-08Z	96	360
Durakote plating	ZD	03310-08ZD	360	720
Zinc-nickel plating	ZN	03310-08ZN	1000	-