



CJ

JIC MALE 74° CONE / JIC FEMALE 74° SEAT RUN TEE
REF. ISO 8434-2

PART NO.	THREAD			DIMENSIONS						
	E	F	G			A	B	C	S1	S2
CJ-04Z	7/16"X20	7/16"X20	7/16"X20			24.5	24.5	9	11	14
CJ-05Z	1/2"X20	1/2"X20	1/2"X20			26.6	26.6	9.5	14	17
CJ-06Z	9/16"X18	9/16"X18	9/16"X18			26.9	26.9	10	14	19
CJ-08Z	3/4"X16	3/4"X16	3/4"X16			32	32	11	19	22
CJ-10Z	7/8"X14	7/8"X14	7/8"X14			37.8	37.8	13	22	27
CJ-12Z	1.1/16"X12	1.1/16"X12	1.1/16"X12			44.2	44.2	14.5	27	32
CJ-14Z	1.3/16"X12	1.3/16"X12	1.3/16"X12			47.5	47.5	15	30	36
CJ-16Z	1.5/16"X12	1.5/16"X12	1.5/16"X12			46	46	15.18	33	41
CJ-20Z	1.5/8"X12	1.5/8"X12	1.5/8"X12			55.5	55.5	16.1	41	50
CJ-24Z	1.7/8"X12	1.7/8"X12	1.7/8"X12			62.5	62.5	18.6	48	60
CJ-32Z	2.1/2"X12	2.1/2"X12	2.1/2"X12			77.5	77.5	23.8	63	75

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	CJ-08Z
304 stainless steel	SR	CJ-08SR
316L stainless steel	SV	CJ-08SV
316Ti stainless steel	SY	CJ-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	CJ-08Z	96	360
Durakote plating	ZD	CJ-08ZD	360	720
Zinc-nickel plating	ZN	CJ-08ZN	1000	-