


6B



6B-LN

BSP MALE 60° SEAT BULKHEAD

PART NO.		THREAD		DIMENSIONS				
BODY	ASSEMBLY	E	F	A	B	L	S1	S2
6B-02Z	6B-02LNZ	G1/8"X28	G1/8"X28	10	33	49	14	14
6B-04Z	6B-04LNZ	G1/4"X19	G1/4"X19	12	35	53	19	19
6B-06Z	6B-06LNZ	G3/8"X19	G3/8"X19	13.5	35	56.5	22	22
6B-08Z	6B-08LNZ	G1/2"X14	G1/2"X14	16	39	65	27	27
6B-10Z	6B-10LNZ	G5/8"X14	G5/8"X14	17.5	40	67.5	30	30
6B-12Z	6B-12LNZ	G3/4"X14	G3/4"X14	18.5	42	71.5	32	32
6B-16Z	6B-16LNZ	G1"X11	G1"X11	20.5	50	84	41	41
6B-20Z	6B-20LNZ	G1.1/4"X11	G1.1/4"X11	20.5	52	89.5	50	50
6B-24Z	6B-24LNZ	G1.1/2"X11	G1.1/2"X11	23	55	93	55	55
6B-32Z	6B-32LNZ	G2"X11	G2"X11	25.5	55	97.5	70	70

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	6B-08Z
304 stainless steel	SR	6B-08SR
316L stainless steel	SV	6B-08SV
316Ti stainless steel	SY	6B-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	6B-08Z	96	360
Durakote plating	ZD	6B-08ZD	360	720
Zinc-nickel plating	ZN	6B-08ZN	1000	-