



METRIC MALE 24° CONE SEAT L SERIES

REF. ISO 12151-2 / DIN 20066

10411
10412

PART NO.		THREAD E	HOSE SIZE		TUBE O.D.	DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S1	
10411-12-04Z	-	M12X1.5	6	04	6	20.5	10	12	
10411-14-04Z *	-	M14X1.5	6	04	8	20.5	10	14	
10411-14-05Z	-	M14X1.5	8	05	8	21.5	10	14	
10411-16-04Z	-	M16X1.5	6	04	10	22.5	11	17	
10411-16-05Z *	-	M16X1.5	8	05	10	22.5	11	17	
10411-16-06Z	10412-16-06Z	M16X1.5	10	06	10	22.5	11	17	
10411-18-05Z	-	M18X1.5	8	05	12	23.5	11	19	
10411-18-06Z *	10412-18-06Z *	M18X1.5	10	06	12	22.5	11	19	
10411-22-06Z	10412-22-06Z	M22X1.5	10	06	15	24.5	12	24	
10411-22-08Z *	10412-22-08Z *	M22X1.5	12	08	15	26	12	24	
10411-26-08Z	10412-26-08Z	M26X1.5	12	08	18	26.5	12	27	
10411-26-10Z *	10412-26-10Z *	M26X1.5	16	10	18	26.5	12	27	
10411-26-12Z	10412-26-12Z	M26X1.5	20	12	18	28	12	27	
10411-30-10Z	10412-30-10Z	M30X2	16	10	22	29.5	14	32	
10411-30-12Z *	10412-30-12Z	M30X2	20	12	22	30	14	32	
10411-36-16Z *	10412-36-16Z	M36X2	25	16	28	31.5	14	38	
10411-45-20Z *	10412N-45-20Z	M45X2	32	20	35	37/39.6	16	46	
10411-52-24Z *	10412N-52-24Z	M52X2	40	24	42	38/41	16	55	

- The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
- Part no. marked with "*" is recommended.
- Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	10411-18-06Z
304 stainless steel	SR	10411-18-06SR
316L stainless steel	SV	10411-18-06SV
316Ti stainless steel	SY	10411-18-06SY

- Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	10411-18-06Z	96	360
Durakote plating	ZD	10411-18-06ZD	360	720
Zinc-nickel plating	ZN	10411-18-06ZN	1000	-