



METRIC MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL

10611Y

10612Y

REF. JIS B8363

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH	A	C	S1	
10611Y-14-04Z	-	M14X1.5	6	04	23.5	11	19	
10611Y-14-06Z	10612Y-14-06Z	M14X1.5	10	06	25	11	19	
10611Y-16-04Z	-	M16X1.5	6	04	27.5	12	22	
10611Y-16-05Z	-	M16X1.5	8	05	27.5	12	22	
10611Y-18-06Z	10612Y-18-06Z	M18X1.5	10	06	27.5	12	24	
10611Y-22-06Z	10612Y-22-06Z	M22X1.5	10	06	30.5	14	27	
10611Y-22-08Z	10612Y-22-08Z	M22X1.5	12	08	31	14	27	
10611Y-24-10Z	10612Y-24-10Z	M24X1.5	16	10	35	14	30	
10611Y-26-10Z	10612Y-26-10Z	M26X1.5	16	10	34.5	16	32	
10611Y-27-10DZ	10612Y-27-10DZ	M27X1.5	16	10	35	16	32	
10611Y-27-10Z	10612Y-27-10Z	M27X2	16	10	34.5	16	32	
10611Y-30-12DZ	10612Y-30-12DZ	M30X1.5	20	12	38	18	36	
10611Y-30-12Z	10612Y-30-12Z	M30X2	20	12	38	18	36	
10611Y-33-16Z	10612Y-33-16Z	M33X2	25	16	40	18	41	
10611Y1-42-20Z +	-	M42X2	32	20	46	20	50	
10611Y-42-20Z ++	10612Y-42-20Z	M42X2	32	20	46/48.6	20	50	
10611Y1-45-20Z +	-	M45X2	32	20	46	20	55	
10611Y-45-20Z ++	10612Y-45-20Z	M45X2	32	20	46/48.6	20	55	
10611Y-48-24Z	10612Y-48-24Z	M48X2	40	24	46/49	20	55	
10611Y-52-24Z	10612Y-52-24Z	M52X2	40	24	46/49	20	60	

- The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
- Part no. marked with "\*" is recommended.
- Marked with "+" design for GH781, GH663, FC686, EC110, EC881 hose, Marked with "++" design for GH793, EC210, EC215 hose.
- The recommended match hoses for 1 piece braided fittings are : FC687/EC115-16 and smaller sizes; GH663/EC881-20 and smaller sizes; FC686/EC210/EC215/GH781-24 and smaller sizes; EC110/GH793 whole sizes etc. and with non-skive crimping. For 1 piece spiral fittings are: 2755/GH493/EC640/GH425-16 and smaller sizes; GH506/EC512-12 and larger sizes with skive crimping.
- Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	10611Y-22-08Z
304 stainless steel	SR	10611Y-22-08SR
316L stainless steel	SV	10611Y-22-08SV
316Ti stainless steel	SY	10611Y-22-08SY

- Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	10611Y-22-08Z	96	360
Durakote plating	ZD	10611Y-22-08ZD	360	720
Zinc-nickel plating	ZN	10611Y-22-08ZN	1000	-