



9F

ORFS FEMALE PLUG

REF. ISO 8434-3

| PART NO. | THREAD | | | | DIMENSIONS | | | | |
|----------|-------------|--|--|--|------------|------|----|--|--|
| | E | | | | A | L | S2 | | |
| 9F-04GMZ | 9/16"X18 | | | | 8.5 | 10.5 | 19 | | |
| 9F-06GMZ | 11/16"X16 | | | | 10 | 13 | 22 | | |
| 9F-08GMZ | 13/16"X16 | | | | 11 | 14 | 27 | | |
| 9F-10GMZ | 1"X14 | | | | 13 | 16 | 30 | | |
| 9F-12GMZ | 1.3/16"X12 | | | | 15 | 15 | 36 | | |
| 9F-16GMZ | 1.7/16"X12 | | | | 15 | 18 | 41 | | |
| 9F-20GMZ | 1.11/16"X12 | | | | 15 | 19 | 50 | | |
| 9F-24GMZ | 2"X12 | | | | 15 | 21 | 60 | | |

1. Material options for connector

| Connector material | Part. No. suffix | Part No. example |
|------------------------|------------------|------------------|
| Carbon steel (Default) | Z | 9F-08GMZ |
| 304 stainless steel | SR | 9F-08GMSR |
| 316L stainless steel | SV | 9F-08GMSV |
| 316Ti stainless steel | SY | 9F-08GMSY |

2. Plating options and performance for carbon steel connectors.

| Plating method | Part. No. suffix | Part No. example | White rust (Hours) | Red rust(Hours) |
|------------------------|------------------|------------------|--------------------|-----------------|
| Cr3+ plating (Default) | Z | 9F-08GMZ | 96 | 360 |
| Durakote plating | ZD | 9F-08GMZD | 360 | 720 |
| Zinc-nickel plating | ZN | 9F-08GMZN | 1000 | - |