



1NO9-OG

NPT MALE/ADJUSTABLE SAE O-RING SEAL 90° ELBOW

PART NO.	THREAD		O-RING	DIMENSIONS			
	E	F	F	A	B	S1	S2
1NO9-02-04OGZ	Z1/8"X27	7/16"X20	O904	18.5	28	11	17
1NO9-02-05OGZ	Z1/8"X27	1/2"X20	O905	23.5	29.9	14	17
1NO9-04-06OGZ	Z1/4"X18	9/16"X18	O906	25.5	31.8	14	19
1NO9-06-08OGZ	Z3/8"X18	3/4"X16	O908	31	37	19	24
1NO9-08-10OGZ	Z1/2"X14	7/8"X14	O910	36.5	44	22	27
1NO9-12OGZ	Z3/4"X14	1.1/16"X12	O912	44	51	27	32
1NO9-12-14OGZ	Z3/4"X14	1.3/16"X12	O914	45	53	30	36
1NO9-16OGZ	Z1"X11.5	1.5/16"X12	O916	50	55	33	41
1NO9-20OGZ	Z1.1/4X11.5	1.5/8"X12	O920	54.5	59.5	41	50

1. Material options for connector and the O-ring.

Connector material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	1NO9-12OGZ
304 stainless steel	Viton	SR	1NO9-12OGSR
316L stainless steel	Viton	SV	1NO9-12OGSV
316Ti stainless steel	Viton	SY	1NO9-12OGSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1NO9-12OGZ	96	360
Durakote plating	ZD	1NO9-12OGZD	360	720
Zinc-nickel plating	ZN	1NO9-12OGZN	1000	-