



1KT-SP

METRIC MALE 60° CONE / BSPT MALE

PART NO.	THREAD		DIMENSIONS					
	E	F	A	B	L	S1		
1KT-14-04SPZ	M14X1.5	R1/4"X19	17	14.5	37.5	14		
1KT-14-06SPZ	M14X1.5	R3/8"X19	17	15	38	17		
1KT-16-06SPZ	M16X1.5	R3/8"X19	18	15	39	17		
1KT-18-06SPZ	M18X1.5	R3/8"X19	18	15	39	19		
1KT-20-06SPZ	M20X1.5	R3/8"X19	20	15	43	22		
1KT-22-06SPZ	M22X1.5	R3/8"X19	20	15	43	24		
1KT-22-08SPZ	M22X1.5	R1/2"X14	20	20	48	24		
1KT-24-08SPZ	M24X1.5	R1/2"X14	21.5	20	51.5	27		
1KT-24-12SPZ	M24X1.5	R3/4"X14	21.5	20	51.5	30		
1KT-30-12SPZ	M30X1.5	R3/4"X14	26	20	57	32		
1KT-33-16SPZ	M33X1.5	R1"X11	30	25.5	66.5	36		
1KT-36-20SPZ	M36X1.5	R1.1/4"X11	33	26.5	72.5	46		
1KT-42-24SPZ	M42X1.5	R1.1/2"X11	36	26.5	77.5	50		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	1KT-22-08SPZ
304 stainless steel	SR	1KT-22-08SPSR
316L stainless steel	SV	1KT-22-08SPSV
316Ti stainless steel	SY	1KT-22-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1KT-22-08SPZ	96	360
Durakote plating	ZD	1KT-22-08SPZD	360	720
Zinc-nickel plating	ZN	1KT-22-08SPZN	1000	-