



7T

BSPT FEMALE

PART NO.	THREAD		DIMENSIONS					
	E	F			L	S1		
7T-02Z	Rc1/8"X28	Rc1/8"X28			20	14		
7T-02-04Z	Rc1/8"X28	Rc1/4"X19			30	19		
7T-04Z	Rc1/4"X19	Rc1/4"X19			30	19		
7T-04-06Z	Rc1/4"X19	Rc3/8"X19			30	22		
7T-04-08Z	Rc1/4"X19	Rc1/2"X14			40	27		
7T-06Z	Rc3/8"X19	Rc3/8"X19			30	22		
7T-06-08Z	Rc3/8"X19	Rc1/2"X14			40	27		
7T-06-12Z	Rc3/8"X19	Rc3/4"X14			37	36		
7T-08Z	Rc1/2"X14	Rc1/2"X14			40	27		
7T-08-12Z	Rc1/2"X14	Rc3/4"X14			42	36		
7T-12Z	Rc3/4"X14	Rc3/4"X14			42	36		
7T-12-16Z	Rc3/4"X14	Rc1"X11			50	41		
7T-16Z	Rc1"X11	Rc1"X11			50	41		
7T-16-20Z	Rc1"X11	Rc1.1/4"X11			52	50		
7T-20Z	Rc1.1/4"X11	Rc1.1/4"X11			55	50		
7T-24Z	Rc1.1/2"X11	Rc1.1/2"X11			55	55		
7T-32Z	Rc2"X11	Rc2"X11			65	70		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	7T-08Z
304 stainless steel	SR	7T-08SR
316L stainless steel	SV	7T-08SV
316Ti stainless steel	SY	7T-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	7T-08Z	96	360
Durakote plating	ZD	7T-08ZD	360	720
Zinc-nickel plating	ZN	7T-08ZN	1000	-