


20511C-T
20512C-T



20511C
20512C

METRIC FEMALE 24° MULTISEAL S SERIES

PART NO.		THREAD E	HOSE SIZE		TUBE O.D.	DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	S2	
20511C-18-04TZ *	-	M18X1.5	6	04	10	21	3	22	
20511C-20-05TZ	-	M20X1.5	8	05	12	21.5	4.5	24	
20511C-20-06TZ *	20512C-20-06TZ	M20X1.5	10	06	12	21.5	4.5	24	
20511C-22-06TZ	20512C-22-06TZ	M22X1.5	10	06	14	21.5	4.5	27	
20511C-24-08TZ *	20512C-24-08TZ	M24X1.5	12	08	16	23	5	30	
20511C-30-10TZ	20512C-30-10TZ	M30X2	16	10	20	26	7	36	
20511C-36-12TZ	20512C-36-12TZ	M36X2	20	12	25	27	6.5	41	
20511C-42-16TZ	20512C-42-16TZ	M42X2	25	16	30	29.5	9	50	
20511C-52-20TZ	20512CN-52-20TZ	M52X2	32	20	38	34/36.6	8	60	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	TZ	20511C-24-08TZ
304 stainless steel	SRT	20511C-24-08SRT
316L stainless steel	SVT	20511C-24-08SVT
316Ti stainless steel	SYT	20511C-24-08SYT

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	20511C-24-08TZ	96	360
Durakote plating	ZD	20511C-24-08TZD	360	720
Zinc-nickel plating	ZN	20511C-24-08TZN	1000	-