



20791
20792

90° GB METRIC FEMALE 74° CONE SEAT

REF. GB/T 9065.5

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH	A	C	S2	
20791-12-04CZ	-	M12X1.25	6	04	30	9	33.5	17
20791-12-04Z	-	M12X1.5	6	04	30	10	33.5	17
20791-14-04Z *	-	M14X1.5	6	04	30	10.5	34	19
20791-16-04Z	-	M16X1.5	6	04	30	10	35	22
20791-16-05Z *	-	M16X1.5	8	05	33	10	38	22
20791-18-06Z *	20792-18-06Z	M18X1.5	10	06	35.3	10	41.3	24
20791-22-08Z *	20792-22-08Z	M22X1.5	12	08	41	10	48	27
20791-22-10Z	20792-22-10Z	M22X1.5	16	10	56	10	52.5	27
20791-27-10Z	20792-27-10Z	M27X1.5	16	10	56	11	54	32
20791-30-12Z	20792-30-12Z	M30X1.5	20	12	66.2	11	63.5	36
20791-33-12Z	20792-33-12Z	M33X2	20	12	65.5	13	63.5	41
20791-33-16Z	20792-33-16Z	M33X2	25	16	76.7	13	69	41
20791-36-12Z	20792-36-12Z	M36X2	20	12	65.5	14	63.5	41
20791-39-16Z	20792-39-16Z	M39X2	25	16	78	14	70.5	46
20791-45-20WZ	20792N-45-20WZ	M45X2	32	20	91.5/94.1	15	86.5	50
20791-52-20WZ	20792N-52-20WZ	M52X2	32	20	93/95.6	17	83.3	60
20791-52-24WZ	20792N-52-24WZ	M52X2	40	24	109.4/112.4	17	100.3	60

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/WZ	20791-22-08Z
304 stainless steel	SR/SRW	20791-22-08SR
316L stainless steel	SV/SVW	20791-22-08SV
316Ti stainless steel	SY/SYW	20791-22-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	20791-22-08Z	96	360
Durakote plating	ZD	20791-22-08ZD	360	720
Zinc-nickel plating	ZN	20791-22-08ZN	1000	-