



2J4

JIC MALE 74° CONE / JIC FEMALE 74° SEAT 45° ELBOW

REF. ISO 8434-2

PART NO.	THREAD		DIMENSIONS							
	E	F			A	B	S1	S2		
2J4-04Z	7/16"X20	7/16"X20			21.5	9	11	14		
2J4-05Z	1/2"X20	1/2"X20			22	9.5	14	17		
2J4-06Z	9/16"X18	9/16"X18			22.8	10	14	19		
2J4-08Z	3/4"X16	3/4"X16			26.8	11	19	22		
2J4-10Z	7/8"X14	7/8"X14			31	13	22	27		
2J4-12Z	1.1/16"X12	1.1/16"X12			35.5	14.5	27	32		
2J4-14Z	1.3/16"X12	1.3/16"X12			37	15	30	36		
2J4-16Z	1.5/16"X12	1.5/16"X12			38.5	15.18	33	41		
2J4-20Z	1.5/8"X12	1.5/8"X12			43	16.18	41	50		
2J4-24Z	1.7/8"X12	1.7/8"X12			49	18.67	48	60		
2J4-32Z	2.1/2"X12	2.1/2"X12			58	23.9	63	75		

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2J4-08Z
304 stainless steel	SR	2J4-08SR
316L stainless steel	SV	2J4-08SV
316Ti stainless steel	SY	2J4-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	2J4-08Z	96	360
Durakote plating	ZD	2J4-08ZD	360	720
Zinc-nickel plating	ZN	2J4-08ZN	1000	-