



**21611**  
**21612**



**21611-T**  
**21612-T**



**21611-W**  
**21612-W**

NPSM FEMALE 60° CONE

END REF. SAE J514 NPSM

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH	A	B	S2	
21611-04-04Z	-	1/4"X18	6	04	18	4.6	19	
21611-04-06Z	21612-04-06Z	1/4"X18	10	06	19	4.6	19	
21611-06-04Z	-	3/8"X18	6	04	19	6	22	
21611-06-05Z	-	3/8"X18	8	05	19	6	22	
21611-06-06Z	21612-06-06Z	3/8"X18	10	06	19	6	22	
21611-08-08Z	21612-08-08Z	1/2"X14	12	08	21.5	7.5	27	
21611-12-10Z	21612-12-10Z	3/4"X14	16	10	24	8.9	32	
21611-12-12Z	21612-12-12Z	3/4"X14	20	12	24	8.9	32	
21611-16-12TZ	21612-16-12TZ	1"X11.5	20	12	25	10.5	41	
21611-16-16Z	21612-16-16Z	1"X11.5	25	16	27	10.5	41	
21611-20-20WZ	21612N-20-20WZ	1.1/4"X11.5	32	20	29.5/32.1	11.1	50	
21611-24-24WZ	21612N-24-24WZ	1.1/2"X11.5	40	24	29.5/32.5	11.2	55	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "\*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/TZ/WZ	21611-08-08Z
304 stainless steel	SR/SRT/SRW	21611-08-08SR
316L stainless steel	SV/SVT/SVW	21611-08-08SV
316Ti stainless steel	SY/SYT/SYW	21611-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	21611-08-08Z	96	360
Durakote plating	ZD	21611-08-08ZD	360	720
Zinc-nickel plating	ZN	21611-08-08ZN	1000	-