



21611
21612



21611-T
21612-T



21611-W
21612-W

NPSM FEMALE 60° CONE

END REF. SAE J514 NPSM

PART NO.		THREAD E	HOSE SIZE			DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	B	S2	
21611-04-04Z	-	1/4"X18	6	04		18	4.6	19	
21611-04-06Z	21612-04-06Z	1/4"X18	10	06		19	4.6	19	
21611-06-04Z	-	3/8"X18	6	04		19	6	22	
21611-06-05Z	-	3/8"X18	8	05		19	6	22	
21611-06-06Z	21612-06-06Z	3/8"X18	10	06		19	6	22	
21611-08-08Z	21612-08-08Z	1/2"X14	12	08		21.5	7.5	27	
21611-12-10Z	21612-12-10Z	3/4"X14	16	10		24	8.9	32	
21611-12-12Z	21612-12-12Z	3/4"X14	20	12		24	8.9	32	
21611-16-12TZ	21612-16-12TZ	1"X11.5	20	12		25	10.5	41	
21611-16-16Z	21612-16-16Z	1"X11.5	25	16		27	10.5	41	
21611-20-20WZ	21612N-20-20WZ	1.1/4"X11.5	32	20		29.5/32.1	11.1	50	
21611-24-24WZ	21612N-24-24WZ	1.1/2"X11.5	40	24		29.5/32.5	11.2	55	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.

2. Part no. marked with "*" is recommended.

3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/TZ/WZ	21611-08-08Z
304 stainless steel	SR/SRT/SRW	21611-08-08SR
316L stainless steel	SV/SVT/SVW	21611-08-08SV
316Ti stainless steel	SY/SYT/SYW	21611-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	21611-08-08Z	96	360
Durakote plating	ZD	21611-08-08ZD	360	720
Zinc-nickel plating	ZN	21611-08-08ZN	1000	-