



45° BSP FEMALE MULTISEAL

22141
22142

22141-T
22142-T

2141-W
2142-W

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH	A	C	H	S2
22141-02-04Z	-	G1/8"X28	6	04	43.7	2	21.6	14
22141-04-03Z	-	G1/4"X19	5	03	41.3	4	20.4	19
22141-04-04Z *	-	G1/4"X19	6	04	43.4	4	21.3	19
22141-06-05Z	-	G3/8"X19	8	05	46.2	5	22.9	22
22141-06-06Z *	22142-06-06Z	G3/8"X19	10	06	47.8	5	23.5	22
22141-06-08Z	22142-06-08Z	G3/8"X19	12	08	60.4	5	25.4	22
22141-08-04TZ	-	G1/2"X14	6	04	43.9	6	23.8	27
22141-08-06TZ	22142-08-06TZ	G1/2"X14	10	06	42.5	6	18.2	27
22141-08-08Z *	22142-08-08Z	G1/2"X14	12	08	62.1	6	27.2	27
22141-08-10Z	22142-08-10Z	G1/2"X14	16	10	72.8	6	28.5	27
22141-10-10Z	22142-10-10Z	G5/8"X14	16	10	73.2	8	28.9	30
22141-10-12Z	22142-10-12Z	G5/8"X14	20	12	79.8	8	32.5	30
22141-12-08TZ	22142-12-08TZ	G3/4"X14	12	08	63.2	9.5	28.3	32
22141-12-10Z	22142-12-10Z	G3/4"X14	16	10	70.4	9.5	29.6	32
22141-12-12Z	22142-12-12Z	G3/4"X14	20	12	80	9	33.2	32
22141-16-12Z	22142-16-12Z	G1"X11	20	12	81.6	11	33.5	41
22141-16-16Z	22142-16-16Z	G1"X11	25	16	89	10.5	34	41
22141-20-16TZ	22142-20-16TZ	G1.1/4"X11	25	16	87.1	9.1	32.9	50
22141-20-20WZ	22142N-20-20WZ	G1.1/4"X11	32	20	99.1/101.7	9.1	38.4	50
22141-24-24WZ	22142N-24-24WZ	G1.1/2"X11	40	24	119.8/122.8	11.5	49	55
22141-32-32WZ	22142N-32-32WZ	G2"X11	50	32	138.4/142.8	15.3	56.2	70

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/TZ/WZ	22141-08-08Z
304 stainless steel	SR/SRT/SRW	22141-08-08SR
316L stainless steel	SV/SVT/SVW	22141-08-08SV
316Ti stainless steel	SY/SYT/SYW	22141-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	22141-08-08Z	96	360
Durakote plating	ZD	22141-08-08ZD	360	720
Zinc-nickel plating	ZN	22141-08-08ZN	1000	-