

5TB-SP

BSPT MALE/BSP FEMALE


PART NO.	THREAD		DIMENSIONS						
	E	F			A	L	S1		
5TB-02-04SPZ	R1/8"X28	G1/4"X19			10	31.5	19		
5TB-04-06SPZ	R1/4"X19	G3/8"X19			14.5	38.5	22		
5TB-04SPZ	R1/4"X19	G1/4"X19			14.5	35	19		
5TB-06-04SPZ	R3/8"X19	G1/4"X19			15	35	19		
5TB-06-08SPZ	R3/8"X19	G1/2"X14			15	43	27		
5TB-06-12SPZ	R3/8"X19	G3/4"X14			15	44	36		
5TB-06SPZ	R3/8"X19	G3/8"X19			15	39	22		
5TB-08-06SPZ	R1/2"X14	G3/8"X19			20	44	22		
5TB-08-12SPZ	R1/2"X14	G3/4"X14			20	50	36		
5TB-08-16SPZ	R1/2"X14	G1"X11			20	52	41		
5TB-08SPZ	R1/2"X14	G1/2"X14			20	48	27		
5TB-12-08SPZ	R3/4"X14	G1/2"X14			20	48	30		
5TB-12-16SPZ	R3/4"X14	G1"X11			20	54.5	41		
5TB-12SPZ	R3/4"X14	G3/4"X14			20	49	36		
5TB-16-12SPZ	R1"X11	G3/4"X14			25.5	55	36		
5TB-16-20SPZ	R1"X11	G1.1/4"X11			25.5	61.5	50		
5TB-16SPZ	R1"X11	G1"X11			25.5	59	41		
5TB-20-08SPZ	R1.1/4"X11	G1/2"X14			26.5	39	46		
5TB-20-12SPZ	R1.1/4"X11	G3/4"X14			26.5	39	46		
5TB-20-24SPZ	R1.1/4"X11	G1.1/2"X11			26.5	63	55		
5TB-20SPZ	R1.1/4"X11	G1.1/4"X11			26.5	61.5	50		
5TB-24-16SPZ	R1.1/2"X11	G1"X11			26.5	40.5	55		
5TB-24-20SPZ	R1.1/2"X11	G1.1/4"X11			26.5	62.5	50		
5TB-24-32SPZ	R1.1/2"X11	G2"X11			26.5	65	70		
5TB-24SPZ	R1.1/2"X11	G1.1/2"X11			26.5	61	55		
5TB-32-24SPZ	R2"X11	G1.1/2"X11			30	61	65		

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5TB-08SPZ
304 stainless steel	SR	5TB-08SPSR
316L stainless steel	SV	5TB-08SPSV
316Ti stainless steel	SY	5TB-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	5TB-08SPZ	96	360



5TB-SP

BSPT MALE/BSP FEMALE

PART NO.	THREAD		DIMENSIONS					
	E	F			A	L	S1	
Durakote plating		ZD	5TB-08SPZD		360		720	
Zinc-nickel plating		ZN	5TB-08SPZN		1000		-	