


6J9



6J9-LN

JIC MALE 74° CONE BULKHEAD 90° ELBOW  
REF. ISO 8434-2

PART NO.		THREAD		DIMENSIONS						
BODY	ASSEMBLY	E	F	A	B	S1	S2			
6J9-04Z	6J9-04LNZ	7/16"X20	7/16"X20	24.5	40.4	11	17			
6J9-05Z	6J9-05LNZ	1/2"X20	1/2"X20	26.6	43.7	14	19			
6J9-06Z	6J9-06LNZ	9/16"X18	9/16"X18	27.7	46	14	22			
6J9-08Z	6J9-08LNZ	3/4"X16	3/4"X16	34.5	53.5	19	24			
6J9-10Z	6J9-10LNZ	7/8"X14	7/8"X14	39.6	60.7	22	30			
6J9-12Z	6J9-12LNZ	1.1/16"X12	1.1/16"X12	45.2	67.8	27	36			
6J9-14Z	6J9-14LNZ	1.3/16"X12	1.3/16"X12	48.2	69.5	30	38			
6J9-16Z	6J9-16LNZ	1.5/16"X12	1.5/16"X12	50	71	33	41			
6J9-20Z	6J9-20LNZ	1.5/8"X12	1.5/8"X12	57.5	79.2	41	50			
6J9-24Z	6J9-24LNZ	1.7/8"X12	1.7/8"X12	62.5	86.9	48	55			

1. Material options for connectory

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	6J9-08Z
304 stainless steel	SR	6J9-08SR
316L stainless steel	SV	6J9-08SV
316Ti stainless steel	SY	6J9-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	6J9-08Z	96	360
Durakote plating	ZD	6J9-08ZD	360	720
Zinc-nickel plating	ZN	6J9-08ZN	1000	-