


**24211DY-SM**



**24212DY-SM**

ORFS FEMALE FLAT SEAT DOUBLE HEXAGON

REF. ISO 12151-1 / SAE J516

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS				
BRAIDED	SPIRAL		DN	DASH	A	C	S1	S2	
NIPPLE WITH SMALLER HEX SIZE AND SEALING SURFACE EXPOSED (STYLE B)									
24211DY-04-04SMZ *	-	9/16"X18	6	04	27.5	8.5	14	17	
24211DY-06-04SMZ	-	11/16"X16	6	04	30	10	17	22	
24211DY-06-06SMZ *	24212DY-06-06SMZ	11/16"X16	10	06	30	10	17	22	
24211DY-08-05SMZ	-	13/16"X16	8	05	33	11	19	24	
24211DY-08-06SMZ	24212DY-08-06SMZ	13/16"X16	10	06	33	11	19	24	
24211DY-08-08SMZ *	24212DY-08-08SMZ *	13/16"X16	12	08	33.5	11	19	24	
24211DY-10-06SMZ	24212DY-10-06SMZ	1"X14	10	06	38	13	24	30	
24211DY-10-08SMZ	24212DY-10-08SMZ	1"X14	12	08	38.5	13	24	30	
24211DY-10-10SMZ	24212DY-10-10SMZ	1"X14	16	10	40	13	24	30	
24211DY-12-12SMZ *	24212DY-12-12SMZ *	1.3/16"X12	20	12	45.3	15	30	36	
24211DY-16-16SMZ	24212DY-16-16SMZ	1.3/16"X12	25	16	48.5	15	36	41	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.

2. Part no. marked with "\*" is recommended.

3. The recommended match hoses for 1 piece braided fittings are : FC687/EC115-16 and smaller sizes; GH663/EC881-20 and smaller sizes; FC686/EC210/EC215/GH781-24 and smaller sizes; EC110/GH793 whole sizes etc. and with non-skive crimping. For 1 piece spiral fittings are: 2755/GH493/EC640/GH425-16 and smaller sizes; GH506/EC512-12 and larger sizes with skive crimping.

4. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	24211DY-08-08SMZ
304 stainless steel	SR	24211DY-08-08SMSR
316L stainless steel	SV	24211DY-08-08SMSV
316Ti stainless steel	SY	24211DY-08-08SMSY

5. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	24211DY-08-08SMZ	96	360
Durakote plating	ZD	24211DY-08-08SMZD	360	720
Zinc-nickel plating	ZN	24211DY-08-08SMZN	1000	-