



JIC FEMALE 74° CONE SEAT

REF. ISO 12151-5 / SAE J516

26711

26711-W

26712

26712-W

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH	A	C	S2	
26711-04-03Z	-	7/16"X20	5	03	14	9	14	
26711-04-04Z *	-	7/16"X20	6	04	15	9	14	
26711-05-04Z	-	1/2"X20	6	04	15.5	9.5	17	
26711-05-05Z *	-	1/2"X20	8	05	15.5	9.5	17	
26711-05-06Z	26712-05-06Z	1/2"X20	10	06	15.5	9.5	17	
26711-06-04Z *	-	9/16"X18	6	04	15.5	10	19	
26711-06-05Z	-	9/16"X18	8	05	15.5	10	19	
26711-06-06Z *	26712-06-06Z	9/16"X18	10	06	15.5	10	19	
26711-06-08Z	26712-06-08Z	9/16"X18	12	08	15.5	10	19	
26711-08-06Z *	26712-08-06Z	3/4"X16	10	06	17.5	11	22	
26711-08-08Z *	26712-08-08Z *	3/4"X16	12	08	18.5	11	22	
26711-08-10Z	26712-08-10Z	3/4"X16	16	10	18	11	22	
26711-10-08Z *	26712-10-08Z	7/8"X14	12	08	19	13	27	
26711-10-10Z *	26712-10-10Z *	7/8"X14	16	10	19.5	13	27	
26711-10-12Z	26712-10-12Z	7/8"X14	20	12	20	13	27	
26711-12-08TZ	26712-12-08TZ	1.1/16"X12	12	08	19.5	15	32	
26711-12-10Z	26712-12-10Z	1.1/16"X12	16	10	21	14.5	32	
26711-12-12Z *	26712-12-12Z *	1.1/16"X12	20	12	21.5	14.5	32	
26711-12-16Z	26712-12-16Z	1.1/16"X12	25	16	23	15	32	
26711-14-12Z	26712-14-12Z	1.3/16"X12	20	12	21.5	15	36	
26711-16-12TZ	26712-16-12TZ	1.5/16"X12	20	12	18.5	16	41	
26711-16-16Z *	26712-16-16Z *	1.5/16"X12	25	16	23	15.2	41	
26711-16-20Z	26712N-16-20Z	1.5/16"X12	32	20	24/26.6	15.2	41	
26711-20-16TZ	26712-20-16TZ	1.5/8"X12	25	16	23	16	50	
26711-20-20WZ *	26712N-20-20WZ	1.5/8"X12	32	20	24.5/27.1	16	50	
26711-24-20WZ	26712N-24-20WZ	1.7/8"X12	32	20	26.5/29.1	18.6	60	
26711-24-24WZ	26712N-24-24WZ	1.7/8"X12	40	24	26.5/29.5	18.6	60	
26711-32-24TZ	26712N-32-24TZ	2.1/2"X12	40	24	27/30	23.5	75	
26711-32-32TZ	26712N-32-32TZ	2.1/2"X12	50	32	27/31.4	23.5	75	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.

2. Part no. marked with "*" is recommended.

3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/TZ/WZ	26711-08-08Z
304 stainless steel	SR/SRT/SRW	26711-08-08SR
316L stainless steel	SV/SVT/SVW	26711-08-08SV
316Ti stainless steel	SY/SYT/SYW	26711-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	26711-08-08Z	96	360
Durakote plating	ZD	26711-08-08ZD	360	720
Zinc-nickel plating	ZN	26711-08-08ZN	1000	-