



JIC FEMALE 74° CONE SEAT DOUBLE HEXAGON

REF. ISO 12151-5 / SAE J516

26711DY-SM

26712DY-SM

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS				
BRAIDED	SPIRAL		DN	DASH	A	C	S1	S2	
NIPPLE WITH SMALLER HEX SIZE									
26711DY-04-04SMZ	-	7/16"-20	6	-04	20	9	12	14	
26711DY-06-04SMZ	-	9/16"-18	6	-04	21	10	14	19	
26711DY-06-06SMZ *	26712DY-06-06SMZ	9/16"-18	10	-06	21	10	17	19	
26711DY-08-06SMZ	26712DY-08-06SMZ	3/4"-16	10	-06	24.5	11	19	22	
26711DY-08-08SMZ *	26712DY-08-08SMZ	3/4"-16	12	-08	23.5	11	19	22	
26711DY-10-08SMZ	26712DY-10-08SMZ	7/8"-14	12	-08	26	13	22	27	
26711DY-10-10SMZ	26712DY-10-10SMZ	7/8"-14	16	-10	27	13	22	27	
26711DY-12-08SMZ *	26712DY-12-08SMZ	1.1/16"-12	12	-08	29.5	15	27	32	
26711DY-12-12SMZ *	26712DY-12-12SMZ	1.1/16"-12	20	-12	31.5	15	27	32	
26711DY-16-16SMWZ	26712DY-16-16SMWZ	1.5/16"-12	25	-16	37.5	15.2	32	41	
26711DY1-20-20SMWZ +	-	1.5/8"-12	32	-20	41	16	41	50	
26711DY-20-20SMWZ ++	26712DY-20-20SMWZ	1.5/8"-12	32	-20	41/45	16	41	50	
26711DY-24-24SMWZ	26712DY-24-24SMWZ	1.7/8"-12	38	-24	42/46	18.6	46	60	
26711DY-32-32SMWZ	26712DY-32-32SMWZ	2.1/2"-12	50	-32	45/50	23.5	65	75	

- The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
- Part no. marked with "*" is recommended.
- Marked with "+" design for GH781, GH663, FC686, EC110, EC881 hose, Marked with "++" design for GH793, EC210, EC215 hose.
- The recommended match hoses for 1 piece braided fittings are : FC687/EC115-16 and smaller sizes; GH663/EC881-20 and smaller sizes; FC686/EC210/EC215/GH781-24 and smaller sizes; EC110/GH793 whole sizes etc. and with non-skive crimping. For 1 piece spiral fittings are: 2755/GH493/EC640/GH425-16 and smaller sizes; GH506/EC512-12 and larger sizes with skive crimping.
- Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/WZ	26711DY-08-08Z
304 stainless steel	SR/SRW	26711DY-08-08SR
316L stainless steel	SV/SVW	26711DY-08-08SV
316Ti stainless steel	SY/SYW	26711DY-08-08SY

6. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	26711DY-08-08Z	96	360
Durakote plating	ZD	26711DY-08-08ZD	360	720
Zinc-nickel plating	ZN	26711DY-08-08ZN	1000	-