



90° JIC COMPACT FEMALE 74° CONE SEAT

REF. ISO 12151-5 / SAE J516

**26791K**

**26792K**

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS				
BRAIDED	SPIRAL		DN	DASH	A	C	H	S1	S2
26791K-04-04Z *	-	7/16"X20	6	04	17.5	9	18	11	14
26791K-06-04Z	-	9/16"X18	6	04	20	10	20.5	14	19
26791K-06-06Z *	26792K-06-06Z	9/16"X18	10	06	20	10	20.5	16	19
26791K-08-06Z	26792K-08-06Z	3/4"X16	10	06	23	11	25	19	22
26791K-08-08Z *	26792K-08-08Z	3/4"X16	12	08	23.5	11	25	22	22
26791K-10-08Z	26792K-10-08Z	7/8"X14	12	08	25	13	27	22	27
26791K-10-10Z	26792K-10-10Z	7/8"X14	16	10	24.5	13	27	22	27
26791K-12-12Z	26792K-12-12Z	1.1/16"X12	20	12	29	15	31	27	32
26791K-16-16Z	26792K-16-16Z	1.5/16"X12	25	16	43	16	34.3	33	41

1. Part no. marked with "\*" is recommended.
2. Carbon steel material for fitting.
3. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	26791K-08-08Z	96	360
Durakote plating	ZD	26791K-08-08ZD	360	720
Zinc-nickel plating	ZN	26791K-08-08ZN	1000	-