



90° JIC COMPACT FEMALE 74° CONE SEAT

REF. ISO 12151-5 / SAE J516

26791KY

| PART NO. | | THREAD E | HOSE SIZE | | DIMENSIONS | | | | |
|------------------|----------------|------------|-----------|------|------------|----|------|----|----|
| BRAIDED | SPIRAL | | DN | DASH | A | C | H | S1 | S2 |
| 26791KY-04-04Z * | - | 7/16"X20 | 6 | 04 | 17.5 | 9 | 18 | 11 | 14 |
| 26791KY-06-04Z | - | 9/16"X18 | 6 | 04 | 20 | 10 | 20.5 | 14 | 19 |
| 26791KY-06-06Z * | 26792KY-06-06Z | 9/16"X18 | 10 | 06 | 20 | 10 | 20.5 | 16 | 19 |
| 26791KY-08-06Z | 26792KY-08-06Z | 3/4"X16 | 10 | 06 | 23 | 11 | 25 | 19 | 22 |
| 26791KY-08-08Z * | 26792KY-08-08Z | 3/4"X16 | 12 | 08 | 23.5 | 11 | 25 | 22 | 22 |
| 26791KY-10-08Z | 26792KY-10-08Z | 7/8"X14 | 12 | 08 | 25 | 13 | 27 | 22 | 27 |
| 26791KY-10-10Z | 26792KY-10-10Z | 7/8"X14 | 16 | 10 | 24.5 | 13 | 27 | 22 | 27 |
| 26791KY-12-12Z | 26792KY-12-12Z | 1.1/16"X12 | 20 | 12 | 29 | 15 | 31 | 27 | 32 |
| 26791KY-16-16Z | 26792KY-16-16Z | 1.5/16"X12 | 25 | 16 | 43 | 16 | 34.3 | 33 | 41 |

1. Part no. marked with "*" is recommended.

2. The recommended match hoses for 1 piece braided fittings are : FC687/EC115-16 and smaller sizes; GH663/EC881-20 and smaller sizes; FC686/EC210/EC215/GH781-24 and smaller sizes; EC110/GH793 whole sizes etc. and with non-skive crimping. For 1 piece spiral fittings are: 2755/GH493/EC640/GH425-16 and smaller sizes; GH506/EC512-12 and larger sizes with skive crimping.

3. Carbon steel material for fitting.

4. Plating options and performance for carbon steel fittings.

| Plating method | Part. No. suffix | Part No. example | White rust (Hours) | Red rust (Hours) |
|------------------------|------------------|------------------|--------------------|------------------|
| Cr3+ plating (Default) | Z | 26791K-08-08Z | 96 | 360 |
| Durakote plating | ZD | 26791K-08-08ZD | 360 | 720 |
| Zinc-nickel plating | ZN | 26791K-08-08ZN | 1000 | - |