


29691
29692



29691-W
29692-W

90° JIS GAS FEMALE 60° CONE SEAT

REF. JIS B8363

PART NO.		THREAD E	HOSE SIZE		DIMENSIONS				
BRAIDED	SPIRAL		DN	DASH	A	C	S1	S2	
29691-04-04Z *	-	G1/4"X19	6	04	30	8	38	19	
29691-04-05Z	-	G1/4"X19	8	05	34	8	41	19	
29691-06-06Z *	29692-06-06Z	G3/8"X19	10	06	35.3	9	45.8	22	
29691-08-08Z *	29692-08-08Z	G1/2"X14	12	08	41	12	53	27	
29691-10-10Z	29692-10-10Z	G5/8"X14	16	10	56	11.5	61	30	
29691-12-12Z	29692-12-12Z	G3/4"X14	20	12	65.5	13.5	69	32	
29691-16-16Z	29692-16-16Z	G1"X11	25	16	76.7	16	76.5	41	
29691-20-20WZ	29692N-20-20WZ	G1.1/4"X11	32	20	91.5/94.1	18.6	92.5	50	
29691-24-24WZ	29692N-24-24WZ	G1.1/2"X11	40	24	109.4/112.4	19	110.5	55	
29691-32-32WZ	29692N-32-32WZ	G2"X11	50	32	131.8/136.2	23	133.8	70	

1. The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
2. Part no. marked with "*" is recommended.
3. Material options for fitting.

Fitting material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z/WZ	29691-08-08Z
304 stainless steel	SR/SRW	29691-08-08SR
316L stainless steel	SV/SVW	29691-08-08SV
316Ti stainless steel	SY/SYW	29691-08-08SY

4. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	29691-08-08Z	96	360
Durakote plating	ZD	29691-08-08ZD	360	720
Zinc-nickel plating	ZN	29691-08-08ZN	1000	-