



2S

JIS GAS MALE/JIS GAS FEMALE

PART NO.	THREAD		DIMENSIONS				
	E	F	A	B	S1	S2	L
2S-02Z	G1/8"X28	G1/8"X28	12	6.5	14	14	26
2S-04Z	G1/4"X19	G1/4"X19	16	8	17	19	30.5
2S-04-06Z	G1/4"X19	G3/8"X19	16	9	17	22	31.5
2S-06-04Z	G3/8"X19	G1/4"X19	18	8	19	19	33.5
2S-06Z	G3/8"X19	G3/8"X19	18	9	19	22	33.5
2S-06-08Z	G3/8"X19	G1/2"X14	18	12	19	27	35
2S-08-06Z	G1/2"X14	G3/8"X19	20	9	22	22	37.5
2S-08Z	G1/2"X14	G1/2"X14	20	12	22	27	39
2S-08-12Z	G1/2"X14	G3/4"X14	20	13.5	27	32	42.5
2S-12-08Z	G3/4"X14	G1/2"X14	22	12	30	27	43
2S-12Z	G3/4"X14	G3/4"X14	22	13.5	30	32	44.5
2S-12-16Z	G3/4"X14	G1"X11	22	16	32	41	47
2S-16-12Z	G1"X11	G3/4"X14	24	13.5	36	32	47.5
2S-16Z	G1"X11	G1"X11	24	16	41	41	51
2S-16-20Z	G1"X11	G1.1/4"X11	24	18.5	41	50	54
2S-20Z	G1.1/4"X11	G1.1/4"X11	27	18.5	46	50	54.5
2S-20-24Z	G1.1/4"X11	G1.1/2"X11	27	19	46	55	57.5
2S-24Z	G1.1/2"X11	G1.1/2"X11	27	19	50	55	59.5

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2S-08Z
304 stainless steel	SR	2S-08SR
316L stainless steel	SV	2S-08SV
316Ti stainless steel	SY	2S-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2S-08Z	96	360
Durakote plating	ZD	2S-08ZD	360	720
Zinc-nickel plating	ZN	2S-08ZN	1000	-