



AJJT-SP

JIC MALE 74° CONE / BSPT MALE RUN TEE

PART NO.	THREAD			DIMENSIONS						
	E	F	G	A	B	C	S1			
AJJT-04-04-02SPZ	7/16"X20	7/16"X20	R1/8"X28	24.5	24.5	21	11			
AJJT-04SPZ	7/16"X20	7/16"X20	R1/4"X19	26.6	26.6	25.5	14			
AJJT-04-04-06SPZ	7/16"X20	7/16"X20	R3/8"X19	27.5	27.5	28	16			
AJJT-06-06-04SPZ	9/16"X18	9/16"X18	R1/4"X19	26.9	26.9	25.5	14			
AJJT-06SPZ	9/16"X18	9/16"X18	R3/8"X19	28.5	28.5	28.5	16			
AJJT-08-08-06SPZ	3/4"X16	3/4"X16	R3/8"X19	32	32	30.5	19			
AJJT-08SPZ	3/4"X16	3/4"X16	R1/2"X14	34.8	34.8	36	22			
AJJT-10-10-08SPZ	7/8"X14	7/8"X14	R1/2"X14	37.8	37.8	36	22			
AJJT-12SPZ	1.1/16"X12	1.1/16"X12	R3/4"X14	44.2	44.2	43.5	27			
AJJT-16SPZ	1.5/16"X12	1.5/16"X12	R1"X11	49	49	50	33			
AJJT-20SPZ	1.5/8"X12	1.5/8"X12	R1.1/4"X11	55.5	55.5	56.5	41			
AJJT-24SPZ	1.7/8"X12	1.7/8"X12	R1.1/2"X11	62.5	62.5	62.5	48			

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	AJJT-08SPZ
304 stainless steel	SR	AJJT-08SPSR
316L stainless steel	SV	AJJT-08SPSV
316Ti stainless steel	SY	AJJT-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	AJJT-08SPZ	96	360
Durakote plating	ZD	AJJT-08SPZD	360	720
Zinc-nickel plating	ZN	AJJT-08SPZN	1000	-