



**5CB-GDK**  
**5DB-GDK**

**5CB-GDK/RN**  
**5DB-GDK/RN**

METRIC MALE 24° CONE/  
BSP PRESSURE GAUGE CONNECTOR WITH DKI SEALING RING

PART NO		THREAD		TUBE O.D.	DIMENSIONS						
BODY	ASSEMBLY	E	F	D1	I1	L1	B	L	S1	S2	SEALING RING DKI
L SERIES											
5CB-12-04GDKZ	5CB-12-04GDKRNWZ	M12X1.5	G1/4"X19	6	10	39.5	14.5	31.5	19	14	DP-B04DK
5CB-14-04GDKZ	5CB-14-04GDKRNWZ	M14X1.5	G1/4"X19	8	6.5	37	14.5	28	19	17	DP-B04DK
5CB-16-04GDKZ	5CB-16-04GDKRNWZ	M16X1.5	G1/4"X19	10	7.5	38	14.5	29	19	19	DP-B04DK
5CB-18-04GDKZ	5CB-18-04GDKRNWZ	M18X1.5	G1/4"X19	12	8.5	38	14.5	30	19	22	DP-B04DK
S SERIES											
5DB-14-08GDKZ	5DB-14-08GDKRNWZ	M14X1.5	G1/2"X14	6	14	49	20	41	27	17	DP-B08DK
5DB-16-08GDKZ	5DB-16-08GDKRNWZ	M16X1.5	G1/2"X14	8	14	50	20	41	27	19	DP-B08DK
5DB-18-08GDKZ	5DB-18-08GDKRNWZ	M18X1.5	G1/2"X14	10	13	49.5	20	40.5	27	22	DP-B08DK
5DB-20-08GDKZ	5DB-20-08GDKRNWZ	M20X1.5	G1/2"X14	12	13	49.5	20	40.5	27	24	DP-B08DK

1. Material options for connector body and nut.

Connector body and nut material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5CB-12-04GDKZ
304 stainless steel	SR	5CB-12-04GDKSR
316L stainless steel	SV	5CB-12-04GDKSV
316Ti stainless steel	SY	5CB-12-04GDKSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	5CB-12-04GDKZ	96	360
Durakote plating	ZD	5CB-12-04GDKZD	360	720
Zinc-nickel plating	ZN	5CB-12-04GDKZN	1000	-