



5JB-GDK

JIC MALE 74° CONE/BSP PRESSURE GAUGE CONNECTOR

PART NO.	THREAD		SEALING RING DKI	DIMENSIONS						
	E	F		A	L	S1				
5JB-04GDKZ	7/16"X20	G1/4"X19	DP-B04DK	14	35.5	19				
5JB-05-04GDKZ	1/2"X20	G1/4"X19	DP-B04DK	14	33	19				
5JB-06-04GDKZ	9/16"X18	G1/4"X19	DP-B04DK	14.1	31.5	19				
5JB-10-08GDKZ	7/8"X14	G1/2"X14	DP-B08DK	19.3	45.5	27				
5JB-12-08GDKZ	1.1/16"X12	G1/2"X14	DP-B08DK	21.9	48	30				

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5JB-06-04GDKZ
304 stainless steel	SR	5JB-06-04GDKSR
316L stainless steel	SV	5JB-06-04GDKSV
316Ti stainless steel	SY	5JB-06-04GDKSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	5JB-06-04GDKZ	96	360
Durakote plating	ZD	5JB-06-04GDKZD	360	720
Zinc-nickel plating	ZN	5JB-06-04GDKZN	1000	-