



10-OG

SAE O-RING BOSS L-SERIES ISO 11926-3

PART NO.	THREAD		O-RING		DIMENSIONS						
	E	F	E	F	A	B	L	S1	S2		
1O-04OGZ	7/16"X20	7/16"X20	O904	O904	9.1	18	33	14	17		
1O-04-06OGZ	7/16"X20	9/16"X18	O904	O906	9.1	20	35.1	17	19		
1O-06OGZ	9/16"X18	9/16"X18	O906	O906	9.93	20	36	17	19		
1O-06-08OGZ	9/16"X18	3/4"X16	O906	O908	9.93	22	40	22	24		
1O-08OGZ	3/4"X16	3/4"X16	O908	O908	11.13	22	40	22	24		
1O-08-12OGZ	3/4"X16	1.1/16"X12	O908	O912	11.13	29	51	32	32		
1O-10OGZ	7/8"X14	7/8"X14	O910	O910	12.7	26	46	27	27		
1O-12OGZ	1.1/16"X12	1.1/16"X12	O912	O912	15.1	29	54	32	32		
1O-16OGZ	1.5/16"X12	1.5/16"X12	O916	O916	15.1	29	54	38	41		
1O-20OGZ	1.5/8"X12	1.5/8"X12	O920	O920	15.1	29	54	50	50		
1O-24OGZ	1.7/8"X12	1.7/8"X12	O924	O924	15.1	29	54	55	55		

1. Material options for connector body and the O-ring.

Connector body material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	1O-08OGZ
304 stainless steel	Viton	SR	1O-08OGSR
316L stainless steel	Viton	SV	1O-08OGSV
316Ti stainless steel	Viton	SY	1O-08OGSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	1O-08OGZ	96	360
Durakote plating	ZD	1O-08OGZD	360	720
Zinc-nickel plating	ZN	1O-08OGZLN	1000	-