



4F

ORFS MALE O-RING PLUG

REF. ISO 8434-3

PART NO.	THREAD	O-RING	DIMENSIONS			
	E	E	A	L	S1	
4F-04Z	9/16"X18	O011	10	16.5	17	
4F-06Z	11/16"X16	O012	11	19	19	
4F-08Z	13/16"X16	O014	13	22	22	
4F-10Z	1"X14	O016	15.5	26	27	
4F-12Z	1.3/16"X12	O018	17	27.5	32	
4F-16Z	1.7/16"X12	O021	17.5	28	41	
4F-20Z	1.11/16"X12	O025	17.5	28	46	
4F-24Z	2"X12	O029	17.5	28	55	

1. Material options for connector body and the O-ring.

Connector body material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	4F-10Z
304 stainless steel	Viton	SR	4F-10SR
316L stainless steel	Viton	SV	4F-10SV
316Ti stainless steel	Viton	SY	4F-10SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4F-10Z	96	360
Durakote plating	ZD	4F-10ZD	360	720
Zinc-nickel plating	ZN	4F-10ZN	1000	-