



NB500

JIC METRIC SLEEVE

REF. ISO 8434-2

PART NO.	THREAD	TUBE O.D.	DIMENSIONS					
			mm	D	L			
NB500-06Z	7/16"X20	6	9.7	10.4				
NB500-08Z	1/2"X20	8	11.3	11.2				
NB500-10Z	9/16"X18	10	12.7	12.7				
NB500-12Z	3/4"X16	12	17.3	14.2				
NB500-14Z	7/8"X14	14	20.2	16.8				
NB500-15Z	7/8"X14	15	20.2	16.8				
NB500-16Z	7/8"X14	16	20.2	16.8				
NB500-18Z	1.1/16"X12	18	24.7	17.3				
NB500-20Z	1.3/16"X12	20	27.8	19.3				
NB500-22Z	1.3/16"X12	22	27.8	19.3				
NB500-25Z	1.5/16"X12	25	31	19.8				
NB500-28Z	1.5/8"X12	28	38.9	23.1				
NB500-30Z	1.5/8"X12	30	38.9	23.1				
NB500-32Z	1.5/8"X12	32	38.9	23.1				
NB500-35Z	1.7/8"X12	35	45.3	28.4				
NB500-38Z	1.7/8"X12	38	45.3	28.4				
NB500-50Z	2.1/2"X12	50	61.2	30.2				

1. Material options for sleeve

Sleeve material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	NB500-08Z
304 stainless steel	SR	NB500-08SR
316L stainless steel	SV	NB500-08SV
316Ti stainless steel	SY	NB500-08SY

2. Plating options and performance for carbon steel sleeves.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	NB500-08Z	96	360
Durakote plating	ZD	NB500-08ZD	360	720
Zinc-nickel plating	ZN	NB500-08ZN	1000	-