



**2B9**

BSP MALE 60° SEAT / BSP FEMALE 60° CONE 90° ELBOW

PART NO.	THREAD		DIMENSIONS					
	E	F	A	B	S1	S2		
2B9-02Z	G1/8"X28	G1/8"X28	19.8	5.5	11	14		
2B9-04Z	G1/4"X19	G1/4"X19	24.5	5.5	14	19		
2B9-04-06Z	G1/4"X19	G3/8"X19	25	6.3	14	22		
2B9-06Z	G3/8"X19	G3/8"X19	27.5	6.3	16	22		
2B9-06-04Z	G3/8"X19	G1/4"X19	27.5	5.5	16	19		
2B9-08Z	G1/2"X14	G1/2"X14	34.5	7.5	22	27		
2B9-08-06Z	G1/2"X14	G3/8"X19	34.5	6.3	22	22		
2B9-10Z	G5/8"X14	G5/8"X14	35	9.5	22	30		
2B9-10-08Z	G5/8"X14	G1/2"X14	35	7.5	22	27		
2B9-12Z	G3/4"X14	G3/4"X14	40	10.9	27	32		
2B9-16Z	G1"X11	G1"X11	46	11.7	33	41		
2B9-20Z	G1.1/4"X11	G1.1/4"X11	50.5	10.1	41	50		
2B9-24Z	G1.1/2"X11	G1.1/2"X11	57.5	12.5	48	55		
2B9-32Z	G2"X11	G2"X11	72.5	16.1	63	70		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2B9-08Z
304 stainless steel	SR	2B9-08SR
316L stainless steel	SV	2B9-08SV
316Ti stainless steel	SY	2B9-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2B9-08Z	96	360
Durakote plating	ZD	2B9-08ZD	360	720
Zinc-nickel plating	ZN	2B9-08ZN	1000	-