



METRIC STANDPIPE STRAIGHT

50011Y

50012Y

REF. GB/T 9065.2

PART NO.		TUBE O.D.	HOSE SIZE		DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH	A	C		
L SERIES								
50011Y-06-03Z	-	6	5	03	28.5	22		
50011Y-06-04Z	-	6	6	04	29	22		
50011Y-10-05Z *	-	10	8	05	31	23		
50011Y-10-06Z	50012Y-10-06Z	10	10	06	32	23		
50011Y-12-06Z *	50012Y-12-06Z	12	10	06	33.5	24		
50011Y-12-08Z	50012Y-12-08Z	12	12	08	33	24		
50011Y-15-06Z	50012Y-15-06Z	15	10	06	35	25		
50011Y-15-08Z *	50012Y-15-08Z	15	12	08	35.5	25		
50011Y-18-08Z	50012Y-18-08Z	18	12	08	36.5	26		
50011Y-18-10Z *	50012Y-18-10Z	18	16	10	40.5	26		
50011Y-22-10Z	50012Y-22-10Z	22	16	10	44.5	28		
50011Y-22-12Z *	50012Y-22-12Z	22	20	12	44	28		
50011Y-22-16Z	50012Y-22-16Z	22	25	16	46	28		
50011Y-28-16Z	50012Y-28-16Z	28	25	16	49	30		
50011Y1-35-20Z +	-	35	32	20	56	36		
50011Y-35-20Z ++	50012Y-35-20Z	35	32	20	56/58.6	36		
50011Y-42-24Z	50012Y-42-24Z	42	40	24	62/65	40		
S SERIES								
50011Y-08-04Z *	-	8	6	04	31	24		
50011Y-08-05Z	-	8	8	05	33	24		
50011Y-08-06Z	50012Y-08-06Z	8	10	06	31.5	24		
50011Y-10-04Z *	-	10	6	04	34	26		
50011Y-12-04Z	-	12	6	04	34.5	26		
50011Y-12-05Z *	-	12	8	05	35.5	26		
50011Y-14-06Z	50012Y-14-06Z	14	10	06	39.5	29		
50011Y-14-08Z	50012Y-14-08Z	14	12	08	40	29		
50011Y-14-12Z	50012Y-14-12Z	14	20	12	45.5	29		
50011Y-16-08Z *	50012Y-16-08Z	16	12	08	41	30		
50011Y-16-10Z	50012Y-16-10Z	16	16	10	45	30		
50011Y-20-10Z *	50012Y-20-10Z	20	16	10	52	36		
50011Y-20-12Z	50012Y-20-12Z	20	20	12	52.5	36		
50011Y-25-12Z	50012Y-25-12Z	25	20	12	56	40		
50011Y-25-16Z	50012Y-25-16Z	25	25	16	57	40		
50011Y-30-16Z	50012Y-30-16Z	30	25	16	63	44		
50011Y1-30-20Z +	-	30	32	20	64	44		
50011Y-30-20Z ++	50012Y-30-20Z	30	32	20	64/66.6	44		
50011Y-38-16Z	50012Y-38-16Z	38	25	16	69	50		
50011Y-38-20Z	50012Y-38-20Z	38	32	20	70/72.6	50		

- The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
- Part no. marked with "*" is recommended.
- Marked with "+" design for GH781, GH663, FC686, EC110, EC881 hose, Marked with "++" design for GH793, EC210, EC215 hose.
- The recommended match hoses for 1 piece braided fittings are : FC687/EC115-16 and smaller sizes; GH663/EC881-20 and smaller sizes; FC686/EC210/EC215/GH781-24 and smaller sizes; EC110/GH793 whole sizes etc. and with non-skive crimping. For 1 piece spiral fittings are: 2755/GH493/EC640/GH425-16 and smaller sizes; GH506/EC512-12 and larger sizes with skive crimping.
- Material options for nipple.

Nipple material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	50011Y-16-08Z
304 stainless steel	SR	50011Y-16-08SR
316L stainless steel	SV	50011Y-16-08SV
316Ti stainless steel	SY	50011Y-16-08SY

- Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	50011Y-16-08Z	96	360
Durakote plating	ZD	50011Y-16-08ZD	360	720
Zinc-nickel plating	ZN	50011Y-16-08ZN	1000	-