



60011Y

60012Y

MT STAPLE-LOK MALE KJ SERIES

REF. MT/T 986 KJ SERIES

PART NO.			HOSE SIZE		O-RING	DIMENSIONS			
BRAIDED	SPIRAL		DN	DASH		A	C	J	K
60011Y-04-04Z *	-		6	04	O7.8X1.9	31	26	15	11
60011Y-05-05Z	-		8	05	O9.8X1.9	33.5	26	18	13
60011Y-06-06Z *	60012Y-06-06Z		10	06	O10.8X2.4	33	26	18	15
60011Y-08-08Z *	60012Y-08-08Z		12	08	O13.8X2.4	34	26	22	18
60011Y-10-10Z	60012Y-10-10Z		16	10	O15.8X2.4	39	30	25	20
60011Y-12-12Z *	60012Y-12-12Z		20	12	O19.8X2.4	40.5	31	28	24
60011Y-16-16Z	60012Y-16-16Z		25	16	O24.4X3.1	42	31	35	30
60011Y1-20-20Z +	-		32	20	O31.7X3.5	43	31	42	38
60011Y-20-20Z ++	60012Y-20-20Z		32	20	O31.7X3.5	43/45.6	31	42	38

- The dimension A before "/" is for braided hose fitting and after "/" is for spiral hose fitting.
- Part no. marked with "*" is recommended.
- Marked with "+" design for GH781, GH663, FC686, EC110, EC881 hose, Marked with "++" design for GH793, EC210, EC215 hose.
- The recommended match hoses for 1 piece braided fittings are : FC687/EC115-16 and smaller sizes; GH663/EC881-20 and smaller sizes; FC686/EC210/EC215/GH781-24 and smaller sizes; EC110/GH793 whole sizes etc. and with non-skive crimping. For 1 piece spiral fittings are: 2755/GH493/EC640/GH425-16 and smaller sizes; GH506/EC512-12 and larger sizes with skive crimping.
- Material options for fitting and the O-ring.

Fitting material	O-ring material	Part. No. suffix	Part No. example
Carbon steel (Default)	NBR	Z	60011Y-08-08Z
304 stainless steel	Viton	SR	60011Y-08-08SR
316L stainless steel	Viton	SV	60011Y-08-08SV
316Ti stainless steel	Viton	SY	60011Y-08-08SY

6. Plating options and performance for carbon steel fittings.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	60011Y-08-08Z	96	360
Durakote plating	ZD	60011Y-08-08ZD	360	720
Zinc-nickel plating	ZN	60011Y-08-08ZN	1000	-