



16011SW

SAE SWIVEL MALE O-RING SEAL LIGHT DUTY

REF. SAE J516 / ISO 11926-3 end

| PART NO. | E THREAD E | HOSE SIZE | | O-RING | DIMENSIONS | | | |
|----------------|---------------|-----------|------|--------|------------|----|--|--|
| | | DN | DASH | | A | S2 | | |
| 16011SW-08-06Z | 3/4"x16 | 10 | 06 | O908 | 57.5 | 27 | | |
| 16011SW-08-08Z | 3/4"x16 | 12 | 08 | O908 | 58 | 27 | | |
| 16011SW-10-08Z | 7/8"x14 | 12 | 08 | O910 | 59.5 | 27 | | |
| 16011SW-10-10Z | 7/8"x14 | 16 | 10 | O910 | 60.1 | 27 | | |
| 16011SW-12-12Z | 1.1/16"x12 | 20 | 12 | O912 | 64.9 | 32 | | |

1. Plating options and performance for carbon steel fittings.

| Plating method | Part. No. suffix | Part No. example | White rust (Hours) | Red rust(Hours) |
|------------------------|------------------|------------------|--------------------|-----------------|
| Cr3+ plating (Default) | Z | 16011SW-08-08Z | 96 | 360 |
| Durakote plating | ZD | 16011SW-08-08ZD | 360 | 720 |
| Zinc-nickel plating | ZN | 16011SW-08-08ZN | 1000 | - |