



2NF

NPT MALE/ORFS FEMALE

PART NO.	THREAD		DIMENSIONS						
	E	F			A	B	L	S1	S2
2NF-02-04Z	Z1/8"X27	9/16"X18			10.5	8.5	32	14	17
2NF-04Z	Z1/4"X18	9/16"X18			15	8.5	36.5	17	17
2NF-04-06Z	Z1/4"X18	11/16"X16			15	10	40.3	17	22
2NF-06Z	Z3/8"X18	11/16"X16			16	10	40.5	19	22
2NF-06-08Z	Z3/8"X18	13/16"X16			16	11	42.5	19	27
2NF-08Z	Z1/2"X14	13/16"X16			19.5	11	48	22	27
2NF-08-10Z	Z1/2"X14	1"X14			19.5	13	52	24	30
2NF-12Z	Z3/4"X14	1.3/16"X12			19.5	15	55.5	30	36
2NF-12-16Z	Z3/4"X14	1.7/16"X12			19.5	15	58.5	36	41
2NF-16Z	Z1"X11.5	1.7/16"X12			25.5	15	64.5	36	41
2NF-16-20Z	Z1"X11.5	1.11/16"X12			25.5	15	70	41	50
2NF-20Z	Z1.1/4"X11.5	1.11/16"X12			26.5	15	70	46	50
2NF-24Z	Z1.1/2"X11.5	2"X12			27.5	15	74	50	60

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2NF-06Z
304 stainless steel	SR	2NF-06SR
316L stainless steel	SV	2NF-06SV
316Ti stainless steel	SY	2NF-06SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2NF-06Z	96	360
Durakote plating	ZD	2NF-06ZD	360	720
Zinc-nickel plating	ZN	2NF-06ZN	1000	-