



90° NPT MALE SWIVEL

**15691KSW**

REF. SAE J516

| PART NO.        | E<br>THREAD E | HOSE SIZE |      | DIMENSIONS |      |    |    |
|-----------------|---------------|-----------|------|------------|------|----|----|
|                 |               | DN        | DASH | A          | H    | S1 | S2 |
| 15691KSW-04-04Z | Z1/4"X18      | 6         | 04   | 25         | 59.5 | 16 | 19 |
| 15691KSW-06-06Z | Z3/8"X18      | 10        | 06   | 25         | 64.5 | 16 | 22 |
| 15691KSW-08-08Z | Z1/2"X14      | 12        | 08   | 28.5       | 71.5 | 19 | 27 |
| 15691KSW-12-12Z | Z3/4"X14      | 20        | 12   | 36         | 76.9 | 27 | 32 |

1. Plating options and performance for carbon steel fittings.

| Plating method         | Part. No. suffix | Part No. example | White rust (Hours) | Red rust(Hours) |
|------------------------|------------------|------------------|--------------------|-----------------|
| Cr3+ plating (Default) | Z                | 15691KSW-08-08Z  | 96                 | 360             |
| Durakote plating       | ZD               | 15691KSW-08-08ZD | 360                | 720             |
| Zinc-nickel plating    | ZN               | 15691KSW-08-08ZN | 1000               | -               |