



4M

METRIC MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL PLUG

PART NO.	THREAD		DIMENSIONS						
		F			B	L	S1		
4M-10Z		M10X1			8	15	14		
4M-12Z		M12X1.5			10	17	17		
4M-14Z		M14X1.5			11	19	19		
4M-16Z		M16X1.5			12	20	22		
4M-18Z		M18X1.5			12	20	24		
4M-20Z		M20X1.5			14	23	27		
4M-22Z		M22X1.5			14	23	27		
4M-24Z		M24X1.5			14	25	30		
4M-26Z		M26X1.5			16	28	32		
4M-27DZ		M27X1.5			16	28	32		
4M-30Z		M30X2			18	29	36		
4M-30DZ		M30X1.5			18	29	36		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	4M-22Z
304 stainless steel	SR	4M-22SR
316L stainless steel	SV	4M-22SV
316Ti stainless steel	SY	4M-22SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	4M-22Z	96	360
Durakote plating	ZD	4M-22ZD	360	720
Zinc-nickel plating	ZN	4M-22ZN	1000	-