



BSP FEMALE 60° CONE

22610

REF. ISO 12151-6

| PART NO. | E THREAD E | HOSE SIZE | | DIMENSIONS | | | |
|--------------|---------------|-----------|------|------------|------|----|--|
| | | DN | DASH | A | D | S2 | |
| 22610-04-04Z | G1/4"X19 | 6 | 04 | 14.7 | 5.5 | 19 | |
| 22610-06-06Z | G3/8"X19 | 10 | 06 | 16.5 | 6.3 | 22 | |
| 22610-08-08Z | G1/2"X14 | 12 | 08 | 18.2 | 7.5 | 27 | |
| 22610-12-12Z | G3/4"X14 | 20 | 12 | 19.9 | 10.9 | 32 | |

1. Material options for nipple.

| Nipple material | Part. No. suffix | Part No. example |
|------------------------|------------------|------------------|
| Carbon steel (Default) | TZ/WZ | 22610-08-08Z |
| 304 stainless steel | SRT/SRW | 22610-08-08SR |
| 316L stainless steel | SVT/SVW | 22610-08-08SV |
| 316Ti stainless steel | SYT/SYW | 22610-08-08SY |

2. Plating options and performance for carbon steel fittings.

| Plating method | Part. No. suffix | Part No. example | White rust (Hours) | Red rust(Hours) |
|------------------------|------------------|------------------|--------------------|-----------------|
| Cr3+ plating (Default) | Z | 22610-08-08Z | 96 | 360 |
| Durakote plating | ZD | 22610-08-08ZD | 360 | 720 |
| Zinc-nickel plating | ZN | 22610-08-08ZN | 1000 | - |