




2TB-SP



BSPT MALE / BSP FEMALE 60° CONE

PART NO.	THREAD		DIMENSIONS					
	E	F	A	B	L	S1	S2	
2TB-02SPZ	R1/8"X28	G1/8"X28	10	5.5	25	12	14	
2TB-04SPZ	R1/4"X19	G1/4"X19	14.5	5.5	31.5	17	19	
2TB-06SPZ	R3/8"X19	G3/8"X19	15	6.3	33	19	22	
2TB-06-04SPZ	R3/8"X19	G1/4"X19	15	5.5	32	19	19	
2TB-06-08SPZ	R3/8"X19	G1/2"X14	15	7.5	35	19	27	
2TB-08SPZ	R1/2"X14	G1/2"X14	20	7.5	42	22	27	
2TB-08-06SPZ	R1/2"X14	G3/8"X19	20	6.3	40	22	22	
2TB-08-12SPZ	R1/2"X14	G3/4"X14	20	10.9	45	27	32	
2TB-12SPZ	R3/4"X14	G3/4"X14	20	10.9	45	30	32	
2TB-12-08SPZ	R3/4"X14	G1/2"X14	20	7.5	44	30	27	
2TB-12-16SPZ	R3/4"X14	G1"X11	20	11.7	47	32	41	
2TB-16SPZ	R1"X11	G1"X11	25.5	11.7	52.5	36	41	
2TB-16-12SPZ	R1"X11	G3/4"X14	25.5	10.9	51.5	36	32	
2TB-20-16SPZ	R1.1/4"X11	G1"X11	26.5	11.7	55.5	46	41	
2TB-20SPZ	R1.1/4"X11	G1.1/4"X11	26.5	10.1	59	46	50	
2TB-24SPZ	R1.1/2"X11	G1.1/2"X11	26.5	12.5	61.5	50	55	
2TB-32SPZ	R2"X11	G2"X11	30	16.1	67	65	70	

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2TB-08SPZ
304 stainless steel	SR	2TB-08SPSR
316L stainless steel	SV	2TB-08SPSV
316Ti stainless steel	SY	2TB-08SPSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2TB-08SPZ	96	360
Durakote plating	ZD	2TB-08SPZD	360	720
Zinc-nickel plating	ZN	2TB-08SPZN	1000	-