



2B-G

BSP MALE 60° SEAT / BSP FEMALE PRESSURE GAUGE CONNECTORS

PART NO.	THREAD		COPPER WASHER	DIMENSIONS				
	E	F		A	B	L	S1	S2
2B-02-04GZ	G1/8"X28	G1/4"X19	DP-B04G	10	12	24.5	14	19
2B-04GZ	G1/4"X19	G1/4"X19	DP-B04G	12	12	26.5	19	19
2B-04-08GZ	G1/4"X19	G1/2"X14	DP-B08G	12	16	29	19	27
2B-06-04GZ	G3/8"X19	G1/4"X19	DP-B04G	13.5	12	30	22	19
2B-08-04GZ	G1/2"X14	G1/4"X19	DP-B04G	16	12	34.5	27	19
2B-08GZ	G1/2"X14	G1/2"X14	DP-B08G	16	16	37	27	27

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2B-08GZ
304 stainless steel	SR	2B-08GSR
316L stainless steel	SV	2B-08GSV
316Ti stainless steel	SY	2B-08GSY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2B-08GZ	96	360
Durakote plating	ZD	2B-08GZD	360	720
Zinc-nickel plating	ZN	2B-08GZN	1000	-