



5JB

JIC MALE 74° CONE/BSP FEMALE

PART NO.	THREAD		DIMENSIONS							
	E	F			A	L	S1			
5JB-04Z	7/16"X20	G1/4"X19			14	35	19			
5JB-04-02Z	7/16"X20	G1/8"X28			14	30.5	14			
5JB-04-06Z	7/16"X20	G3/8"X19			14	35.5	22			
5JB-04-08Z	7/16"X20	G1/2"X14			14	40	27			
5JB-06Z	9/16"X18	G3/8"X19			14.1	37	22			
5JB-06-04Z	9/16"X18	G1/4"X19			14.1	35.5	19			
5JB-06-08Z	9/16"X18	G1/2"X14			14.1	42	27			
5JB-06-10Z	9/16"X18	G5/8"X14			14.1	43.4	30			
5JB-08Z	3/4"X16	G1/2"X14			16.7	46	27			
5JB-08-04Z	3/4"X16	G1/4"X19			16.7	38.5	22			
5JB-08-06Z	3/4"X16	G3/8"X19			16.7	40	22			
5JB-08-10Z	3/4"X16	G5/8"X14			16.7	45.7	30			
5JB-08-12Z	3/4"X16	G3/4"X14			16.7	46	32			
5JB-10-08Z	7/8"X14	G1/2"X14			19.3	48	27			
5JB-10-12Z	7/8"X14	G3/4"X14			19.3	48	32			
5JB-12Z	1.1/16"X12	G3/4"X14			21.9	52	36			
5JB-12-08Z	1.1/16"X12	G1/2"X14			21.9	50	30			
5JB-12-10Z	1.1/16"X12	G5/8"X14			21.9	51.1	30			
5JB-12-16Z	1.1/16"X12	G1"X11			21.9	53	41			
5JB-16Z	1.5/16"X12	G1"X11			23.1	58	41			
5JB-16-12Z	1.5/16"X12	G3/4"X14			23.1	50	36			
5JB-16-20Z	1.5/16"X12	G1.1/4"X11			23.1	57	50			
5JB-16-24Z	1.5/16"X12	G1.1/2"X11			23.1	59.6	55			
5JB-20Z	1.5/8"X12	G1.1/4"X11			24.3	63	50			
5JB-20-16Z	1.5/8"X12	G1"X11			24.3	59.5	46			
5JB-20-24Z	1.5/8"X12	G1.1/2"X11			24.3	64.8	55			
5JB-24Z	1.7/8"X12	G1.1/2"X11			27.5	67	55			
5JB-24-20Z	1.7/8"X12	G1.1/4"X11			27.5	66	50			
5JB-24-32Z	1.7/8"X12	G2"X11			27.5	68	70			
5JB-32Z	2.1/2"X12	G2"X11			33.9	67	70			

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5JB-08Z
304 stainless steel	SR	5JB-08SR
316L stainless steel	SV	5JB-08SV
316Ti stainless steel	SY	5JB-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	5JB-08Z	96	360
Durakote plating	ZD	5JB-08ZD	360	720
Zinc-nickel plating	ZN	5JB-08ZN	1000	-