



**2NU9**

NPT MALE / NPSM FEMALE 60° CONE 90° ELBOW

PART NO.	THREAD		DIMENSIONS					
	E	F	A	B	S1	S2		
2NU9-02Z	Z1/8"X27	1/8"X27	18.5	3.5	11	15		
2NU9-02-04Z	Z1/8"X27	1/4"X18	21	4.6	11	19		
2NU9-04-02Z	Z1/4"X18	1/8"X27	25.5	3.5	14	15		
2NU9-04Z	Z1/4"X18	1/4"X18	25.5	4.6	14	19		
2NU9-04-06Z	Z1/4"X18	3/8"X18	25.5	6	14	22		
2NU9-06Z	Z3/8"X18	3/8"X18	31	6	19	22		
2NU9-06-04Z	Z3/8"X18	1/4"X18	31	4.6	19	19		
2NU9-06-08Z	Z3/8"X18	1/2"X14	31	7.5	19	27		
2NU9-08Z	Z1/2"X14	1/2"X14	37.3	7.5	22	27		
2NU9-08-06Z	Z1/2"X14	3/8"X18	36.7	6	22	22		
2NU9-08-12Z	Z1/2"X14	3/4"X14	37.5	8.9	24	32		
2NU9-12Z	Z3/4"X14	3/4"X14	44	8.9	27	32		
2NU9-12-08Z	Z3/4"X14	1/2"X14	44	7.5	27	27		
2NU9-12-16Z	Z3/4"X14	1"X11.5	45	10.5	30	41		
2NU9-16Z	Z1"X11.5	1"X11.5	50	10.5	33	41		
2NU9-16-12Z	Z1"X11.5	3/4"X14	50	8.9	33	32		
2NU9-20-16Z	Z1.1/4"X11.5	1"X11.5	54.5	10.5	41	41		
2NU9-20Z	Z1.1/4"X11.5	1.1/4"X11.5	54.5	11.2	41	50		
2NU9-24Z	Z1.1/2"X11.5	1.1/2"X11.5	59.5	11.2	48	55		
2NU9-32Z	Z2"X11.5	2"X11.5	73.5	11.2	63	70		

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2NU9-08Z
304 stainless steel	SR	2NU9-08SR
316L stainless steel	SV	2NU9-08SV
316Ti stainless steel	SY	2NU9-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2NU9-08Z	96	360
Durakote plating	ZD	2NU9-08ZD	360	720
Zinc-nickel plating	ZN	2NU9-08ZN	1000	-