

**5B-G**

BSP MALE DOUBLE USE FOR 60° CONE SEAT OR BONDED SEAL / BSP
FEMALE PRESSURE GAUGE CONNECTORS

PART NO.	THREAD		COPPER WASHER	DIMENSIONS				
	E	F		A	B	L	S1	
5B-04GZ	G1/4"x19	G1/4"X19	DP-B04G	12	11	26	19	
5B-06-04GZ	G3/8"x19	G1/4"X19	DP-B04G	13.5	11	28.5	22	
5B-06-08GZ	G3/8"x19	G1/2"X14	DP-B08G	13.5	17	35.5	27	
5B-08GZ	G1/2"x14	G1/2"X14	DP-B08G	16	17	37	27	

1. Material options for connector body

Connector boy material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5B-08GZ
304 stainless steel	SR	5B-08GSR
316L stainless steel	SV	5B-08GSV
316Ti stainless steel	SY	5B-08GSY

2. Plating options and performance for carbon steel adaptors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	5B-08GZ	96	360
Durakote plating	ZD	5B-08GZD	360	720
Zinc-nickel plating	ZN	5B-08GZN	1000	-