



2NU

NPT MALE / NPSM FEMALE 60° CONE

PART NO.	THREAD		DIMENSIONS						
	E	F			A	B	L	S1	S2
2NU-02Z	Z1/8"X27	1/8"X27			10.5	3.5	25.5	12	15
2NU-02-04Z	Z1/8"X27	1/4"X18			10.5	4.6	27.5	12	19
2NU-04-02Z	Z1/4"X18	1/8"X27			15	3.5	30	14	15
2NU-04Z	Z1/4"X18	1/4"X18			15	4.6	32	17	19
2NU-04-06Z	Z1/4"X18	3/8"X18			15	6	33	17	22
2NU-04-08Z	Z1/4"X18	1/2"X14			15	7.5	35	19	27
2NU-06Z	Z3/8"X18	3/8"X18			16	6	34.5	19	22
2NU-06-04Z	Z3/8"X18	1/4"X18			16	4.6	33	19	19
2NU-06-08Z	Z3/8"X18	1/2"X14			16	7.5	36	19	27
2NU-08Z	Z1/2"X14	1/2"X14			19.5	7.5	41.5	22	27
2NU-08-04Z	Z1/2"X14	1/4"X18			19.5	4.6	38.5	22	19
2NU-08-06Z	Z1/2"X14	3/8"X18			19.5	6	39.5	22	22
2NU-12Z	Z3/4"X14	3/4"X14			19.5	8.9	44.5	30	32
2NU-12-06Z	Z3/4"X14	3/8"X18			19.5	6	41.5	30	22
2NU-12-08Z	Z3/4"X14	1/2"X14			19.5	7.5	43.5	30	27
2NU-12-16Z	Z3/4"X14	1"X11.5			19.5	10.5	46.5	32	41
2NU-16-12Z	Z1"X11.5	3/4"X14			21.5	8.9	51.5	36	32
2NU-16Z	Z1"X11.5	1"X11.5			25.5	10.5	52.5	36	41
2NU-16-20Z	Z1"X11.5	1.1/4"X11.5			25.5	11.2	58.5	41	50
2NU-20-16Z	Z1.1/4"X11.5	1"X11.5			26.5	10.5	55.5	46	41
2NU-20Z	Z1.1/4"X11.5	1.1/4"X11.5			26.5	11.2	59.5	46	50
2NU-20-24Z	Z1.1/4"X11.5	1.1/2"X11.5			26.5	11.2	59.5	46	55
2NU-24-20Z	Z1.1/2"X11.5	1.1/4"X11.5			27.5	11.2	62.5	50	50
2NU-24Z	Z1.1/2"X11.5	1.1/2"X11.5			27.5	11.2	62.5	50	55
2NU-32Z	Z2"X11.5	2"X11.5			27.5	11.2	64.5	65	70

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2NU-12Z
304 stainless steel	SR	2NU-12SR
316L stainless steel	SV	2NU-12SV
316Ti stainless steel	SY	2NU-12SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2NU-12Z	96	360
Durakote plating	ZD	2NU-12ZD	360	720
Zinc-nickel plating	ZN	2NU-12ZN	1000	-