



BJ

JIC MALE 74° CONE / JIC FEMALE 74° SEAT BRANCH TEE

REF. ISO 8434-2

PART NO.	THREAD			DIMENSIONS						
	E	F	G			A	B	C	S1	S2
BJ-04Z	7/16"X20	7/16"X20	7/16"X20			24.5	9	24.5	11	14
BJ-05Z	1/2"X20	1/2"X20	1/2"X20			26.5	9.5	26.5	14	17
BJ-06Z	9/16"X18	9/16"X18	9/16"X18			26.9	10	26.9	14	19
BJ-08Z	3/4"X16	3/4"X16	3/4"X16			32	11	32	19	22
BJ-10Z	7/8"X14	7/8"X14	7/8"X14			37.8	13	37.8	22	27
BJ-12Z	1.1/16"X12	1.1/16"X12	1.1/16"X12			44.2	14.5	44.2	27	32
BJ-14Z	1.3/16"X12	1.3/16"X12	1.3/16"X12			47.5	15	47.5	30	36
BJ-16Z	1.5/16"X12	1.5/16"X12	1.5/16"X12			49	15.18	49	33	41
BJ-20Z	1.5/8"X12	1.5/8"X12	1.5/8"X12			56	16.1	56	41	50
BJ-24Z	1.7/8"X12	1.7/8"X12	1.7/8"X12			63.5	18.6	63.5	48	60
BJ-32Z	2.1/2"X12	2.1/2"X12	2.1/2"X12			78	23.8	78	63	75

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	BJ-08Z
304 stainless steel	SR	BJ-08SR
316L stainless steel	SV	BJ-08SV
316Ti stainless steel	SY	BJ-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	BJ-08Z	96	360
Durakote plating	ZD	BJ-08ZD	360	720
Zinc-nickel plating	ZN	BJ-08ZN	1000	-