



2NB

NPT MALE / BSP FEMALE 60° CONE

PART NO.	THREAD		DIMENSIONS						
	E	F			A	B	L	S1	S2
2NB-02Z	Z1/8"X27	G1/8"X28			10.5	5.5	25.5	12	14
2NB-02-04Z	Z1/8"X27	G1/4"X19			10.5	5.5	27	14	19
2NB-04Z	Z1/4"X18	G1/4"X19			15	5.5	31	17	19
2NB-04-06Z	Z1/4"X18	G3/8"X19			15	6.3	32.5	17	22
2NB-04-08Z	Z1/4"X18	G1/2"X14			15	7.5	35	19	27
2NB-06Z	Z3/8"X18	G3/8"X19			16	6.3	33.5	19	22
2NB-06-08Z	Z3/8"X18	G1/2"X14			16	7.5	36	19	27
2NB-08Z	Z1/2"X14	G1/2"X14			19.5	7.5	41	22	27
2NB-08-06Z	Z1/2"X14	G3/8"X19			19.5	6.3	39.5	24	22
2NB-08-12Z	Z1/2"X14	G3/4"X14			19.5	10.9	44.5	27	32
2NB-12Z	Z3/4"X14	G3/4"X14			19.5	10.9	44.5	30	32
2NB-12-16Z	Z3/4"X14	G1"X11			19.5	11.7	46.5	32	41
2NB-16Z	Z1"X11.5	G1"X11			25.5	11.7	52.5	36	41
2NB-16-20Z	Z1"X11.5	G1.1/4"X11			25.5	10.1	59.5	41	50
2NB-20Z	Z1.1/4"X11.5	G1.1/4"X11			26.5	10.1	59.5	46	50
2NB-24Z	Z1.1/2"X11.5	G1.1/2"X11			27.5	12.5	62	50	55
2NB-32Z	Z2"X11.5	G2"X11			27.5	16.1	64.5	65	70

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	2NB-08Z
304 stainless steel	SR	2NB-08SR
316L stainless steel	SV	2NB-08SV
316Ti stainless steel	SY	2NB-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	2NB-08Z	96	360
Durakote plating	ZD	2NB-08ZD	360	720
Zinc-nickel plating	ZN	2NB-08ZN	1000	-