



5NT

NPT MALE/BSPT FEMALE

PART NO.	THREAD		DIMENSIONS					
	E	F			A	L	S1	
5NT-04Z	Z1/4"X18	Rc1/4"X19			15	34.5	19	
5NT-04-02Z	Z1/4"X18	Rc1/8"X28			15	21	14	
5NT-04-06Z	Z1/4"X18	Rc3/8"X19			15	37	22	
5NT-06Z	Z3/8"X18	Rc3/8"X19			16	37.5	22	
5NT-06-04Z	Z3/8"X18	Rc1/4"X19			16	22	19	
5NT-06-08Z	Z3/8"X18	Rc1/2"X14			16	43	27	
5NT-08Z	Z1/2"X14	Rc1/2"X14			19.5	46	27	
5NT-08-06Z	Z1/2"X14	Rc3/8"X19			19.5	29.5	24	
5NT-08-12Z	Z1/2"X14	Rc3/4"X14			19.5	50	36	
5NT-12Z	Z3/4"X14	Rc3/4"X14			19.5	46	36	
5NT-12-08Z	Z3/4"X14	Rc1/2"X14			19.5	29.5	27	
5NT-12-16Z	Z3/4"X14	Rc1"X11			19.5	52	41	
5NT-16Z	Z1"X11.5	Rc1"X11			25.5	57	41	
5NT-16-12Z	Z1"X11.5	Rc3/4"X14			25.5	51	36	
5NT-16-20Z	Z1"X11.5	Rc1.1/4"X11			25.5	63.5	50	
5NT-20Z	Z1.1/4"X11.5	Rc1.1/4"X11			26.5	64.5	50	
5NT-20-16Z	Z1.1/4"X11.5	Rc1"X11			26.5	39.5	46	
5NT-20-24Z	Z1.1/4"X11.5	Rc1.1/2"X11			26.5	64.5	55	
5NT-24Z	Z1.1/2"X11.5	Rc1.1/2"X11			27.5	65.5	55	
5NT-32Z	Z2"X11.5	Rc2"X11			27.5	65	70	

1. Material options for connector.

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	5NT-12Z
304 stainless steel	SR	5NT-12SR
316L stainless steel	SV	5NT-12SV
316Ti stainless steel	SY	5NT-12SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust(Hours)
Cr3+ plating (Default)	Z	5NT-12Z	96	360
Durakote plating	ZD	5NT-12ZD	360	720
Zinc-nickel plating	ZN	5NT-12ZN	1000	-