



**LJNN**

JIC MALE 74° CONE / NPT MALE / NPT FEMALE TEE

PART NO.	THREAD			DIMENSIONS					
	E	F	G		A	B	C	S1	
LJNN-04Z	7/16"X20	Z1/4"X18	Z1/4"X18		29.5	28	22.4	19	
LJNN-04-02-02Z	7/16"X20	Z1/8"X27	Z1/8"X27		27.5	24.5	16.8	16	
LJNN-06Z	9/16"X18	Z3/8"X18	Z3/8"X18		33.5	33.5	25.9	24	
LJNN-06-04-04Z	9/16"X18	Z1/4"X18	Z1/4"X18		31.2	28	22.4	19	
LJNN-08Z	3/4"X16	Z1/2"X14	Z1/2"X14		39.5	41.2	31.2	30	
LJNN-08-06-06Z	3/4"X16	Z3/8"X18	Z3/8"X18		36	33.5	25.9	24	
LJNN-10-08-08Z	7/8"X14	Z1/2"X14	Z1/2"X14		42.5	41.2	31.2	30	
LJNN-12Z	1.1/16"X12	Z3/4"X14	Z3/4"X14		48	45.2	34.5	33	
LJNN-14-12-12Z	1.3/16"X12	Z3/4"X14	Z3/4"X14		48.5	45.2	34.5	33	
LJNN-16Z	1.5/16"X12	Z1"X11.5	Z1"X11.5		55.1	54.5	41.1	41	

1. Material options for connector

Connector material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	LJNN-08Z
304 stainless steel	SR	LJNN-08SR
316L stainless steel	SV	LJNN-08SV
316Ti stainless steel	SY	LJNN-08SY

2. Plating options and performance for carbon steel connectors.

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	LJNN-08Z	96	360
Durakote plating	ZD	LJNN-08ZD	360	720
Zinc-nickel plating	ZN	LJNN-08ZN	1000	-